



DADOS TÉCNICOS

Referência: 09512330; 09512331; 09512332; 09512333; 09512334; 09512335; 09512336; 09512337; 09512338; 09512339; 09512340; 09512341; 09512342; 09512343; 09512344; 09512345; 09512346; 09512347; 09512348; 09512349; 09512350; 09512351; 09512352; 09512353; 09512354; 09512355

Chaves de porcas abertas: Acabamento polido espelhado: Tamanhos SW 6 a SW 32



Chaves de porcas abertas com acabamento polido espelhado.

Tamanhos de SW 6 a SW 32.

Perfil de 6 lados para uma maior superfície de contacto, garantindo uma maior aderência e maior resistência.

Fabricada em aço cromo-vanádio de alta resistência e qualidade.

Possibilidade de passar uma haste rosada ou um pino sem prejudicar a resistência da chave.



DADOS TÉCNICOS



cofan



cofan



cofan

Ref	⊖	⊕	⊗	⊗⊗
0951 2330	6 mm	1	5	✓
0951 2331	7 mm	1	5	✓
0951 2332	8 mm	1	5	✓
0951 2333	9 mm	1	5	✓
0951 2334	10 mm	1	5	✓
0951 2335	11 mm	1	5	✓
0951 2336	12 mm	1	5	✓
0951 2337	13 mm	1	5	✓
0951 2338	14 mm	1	5	✓
0951 2339	15 mm	1	5	✓
0951 2340	16 mm	1	5	✓
0951 2341	17 mm	1	5	✓
0951 2342	18 mm	1	5	✓
0951 2343	19 mm	1	5	✓
0951 2344	20 mm	1	5	✓
0951 2345	21 mm	1	5	✓
0951 2346	22 mm	1	5	✓
0951 2347	23 mm	1	1	✓
0951 2348	24 mm	1	1	✓
0951 2349	25 mm	1	1	✓
0951 2350	26 mm	1	1	✓
0951 2351	27 mm	1	1	✓
0951 2352	28 mm	1	1	✓
0951 2353	29 mm	1	1	✓
0951 2354	30 mm	1	1	✓
0951 2355	32 mm	1	1	✓