

FICHA TÉCNICA

Referencias: 09691000; 09691050; 09691100; 09691150; 09691200; 09691250; 09691300; 09691350; 09691400; 09691450; 09691500; 09691550; 09691600; 09691650; 09691700; 09691750; 09691800; 09691850; 09691900; 09691950; 09692000; 09692050; 09692100; 09692150; 09692200; 09692250; 09692300; 09692350; 09692400; 09692450; 09692500; 09692550; 09692600; 09692650; 09692700; 09692750; 09692800; 09692850; 09692900; 09692950; 09693000; 09693100; 09693200; 09693300; 09693400; 09693500; 09693600; 09693700; 09693800; 09693900; 09694000

Brocas mango cónico cobalto HSS-CO DIN 345N

HSS-CO



Broca de Cobalto con mango cónico "Cono Morse" de acero rápido HSS CO rectificada y punta de 118º, afiladas.



FICHA TÉCNICA



P

Ref	Ø	↔	P		
0969 1000	10 mm	168 mm	87 mm	1	1
0969 1050	10,5 mm	168 mm	87 mm	1	1
0969 1100	11 mm	175 mm	94 mm	1	1
0969 1150	11,5 mm	175 mm	94 mm	1	1
0969 1200	12 mm	182 mm	101 mm	1	1
0969 1250	12,5 mm	182 mm	101 mm	1	1
0969 1300	13 mm	182 mm	101 mm	1	1
0969 1350	13,5 mm	189 mm	108 mm	1	1
0969 1400	14 mm	189 mm	108 mm	1	1
0969 1450	14,5 mm	212 mm	114 mm	2	1
0969 1500	15 mm	212 mm	114 mm	2	1
0969 1550	15,5 mm	218 mm	120 mm	2	1
0969 1600	16 mm	218 mm	120 mm	2	1
0969 1650	16,5 mm	223 mm	125 mm	2	1
0969 1700	17 mm	223 mm	125 mm	2	1
0969 1750	17,5 mm	228 mm	130 mm	2	1
0969 1800	18 mm	228 mm	130 mm	2	1
0969 1850	18,5 mm	233 mm	135 mm	2	1
0969 1900	19 mm	233 mm	135 mm	2	1
0969 1950	19,5 mm	238 mm	140 mm	2	1
0969 2000	20 mm	238 mm	140 mm	2	1
0969 2050	20,5 mm	243 mm	145 mm	2	1
0969 2100	21 mm	243 mm	145 mm	2	1
0969 2150	21,5 mm	248 mm	150 mm	2	1
0969 2200	22 mm	248 mm	150 mm	2	1
0969 2250	22,5 mm	253 mm	155 mm	2	1



FICHA TÉCNICA



P

Ref	Ø	↔	P		
0969 2300	23 mm	253 mm	155 mm	3	1
0969 2350	23,5 mm	276 mm	155 mm	3	1
0969 2400	24 mm	281 mm	160 mm	3	1
0969 2450	24,5 mm	281 mm	160 mm	3	1
0969 2500	25 mm	281 mm	160 mm	3	1
0969 2550	25,5 mm	286 mm	165 mm	3	1
0969 2600	26 mm	286 mm	165 mm	3	1
0969 2650	26,5 mm	286 mm	165 mm	3	1
0969 2700	27 mm	291 mm	170 mm	3	1
0969 2750	27,5 mm	291 mm	170 mm	3	1
0969 2800	28 mm	291 mm	170 mm	3	1
0969 2850	28,5 mm	296 mm	175 mm	3	1
0969 2900	29 mm	296 mm	175 mm	3	1
0969 2950	29,5 mm	296 mm	175 mm	3	1
0969 3000	30 mm	296 mm	175 mm	3	1
0969 3100	31 mm	301 mm	180 mm	3	1
0969 3200	32 mm	334 mm	185 mm	4	1
0969 3300	33 mm	334 mm	185 mm	4	1
0969 3400	34 mm	339 mm	190 mm	4	1
0969 3500	35 mm	339 mm	190 mm	4	1
0969 3600	36 mm	344 mm	195 mm	4	1
0969 3700	37 mm	344 mm	195 mm	4	1
0969 3800	38 mm	349 mm	200 mm	4	1
0969 3900	39 mm	349 mm	200 mm	4	1
0969 4000	40 mm	349 mm	200 mm	4	1