



CARACTÉRISTIQUES TECHNIQUES

Référence: 09730100; 09730150; 09730200; 09730225; 09730250; 09730275; 09730300; 09730325; 09730350; 09730375; 09730400; 09730425; 09730450; 09730475; 09730500; 09730525; 09730550; 09730575; 09730600; 09730625; 09730650; 09730700; 09730750; 09730775; 09730800; 09730825; 09730850; 09730875; 09730900; 09730950; 09731000; 09731025; 09731050; 09731075; 09731100; 09731150; 09731200; 09731250; 09731300; 09731350; 09731400; 09731450; 09731500; 09731550; 09731600; 09731650; 09731700; 09731725; 09731750; 09731800; 09731850; 09731900; 09731950; 09732000; 09730070; 09730080; 09730090

Couronnes de métal dur

HSS



Mèches HSS HSS rectifiées DIN 338N 118°.

Pour l'acier et le fer.
Couleur noire



CARACTERÍSTICAS TÉCNICAS

Ref	Ø	
0973 0070	0,7 mm	10
0973 0080	0,8 mm	10
0973 0090	0,9 mm	10
0973 0100	1,0 mm	10
0973 0150	1,5 mm	10
0973 0200	2,0 mm	10
0973 0225	2,25 mm	10
0973 0250	2,5 mm	10
0973 0275	2,75 mm	10
0973 0300	3,0 mm	10
0973 0325	3,25 mm	10
0973 0350	3,5 mm	10
0973 0375	3,75 mm	10
0973 0400	4,0 mm	10
0973 0425	4,25 mm	10
0973 0450	4,5 mm	10
0973 0475	4,75 mm	10
0973 0500	5,0 mm	10
0973 0525	5,25 mm	10

Ref	Ø	
0973 0550	5,5 mm	10
0973 0575	5,75 mm	10
0973 0600	6,0 mm	10
0973 0625	6,25 mm	10
0973 0650	6,5 mm	10
0973 0700	7,0 mm	10
0973 0750	7,5 mm	10
0973 0775	7,75 mm	10
0973 0800	8,0 mm	10
0973 0825	8,25 mm	10
0973 0850	8,5 mm	10
0973 0875	8,75 mm	10
0973 0900	9,0 mm	10
0973 0950	9,5 mm	10
0973 1000	10,0 mm	5
0973 1025	10,25 mm	5
0973 1050	10,5 mm	5
0973 1075	10,75 mm	5
0973 1100	11,0 mm	5



CARACTÉRISTIQUES TECHNIQUES

Ref	Ø	
0973 1150	11,5 mm	5
0973 1200	12,0 mm	5
0973 1250	12,5 mm	5
0973 1300	13,0 mm	5
0973 1350	13,5 mm	4
0973 1400	14,0 mm	4
0973 1450	14,5 mm	4
0973 1500	15,0 mm	4
0973 1550	15,5 mm	1
0973 1600	16,0 mm	1
0973 1650	16,5 mm	1
0973 1700	17,0 mm	1
0973 1725	17,25 mm	1
0973 1750	17,5 mm	1
0973 1800	18,0 mm	1
0973 1850	18,5 mm	1
0973 1900	19,0 mm	1
0973 1950	19,5 mm	1
0973 2000	20,0 mm	1