



DADOS TÉCNICOS

Referência: 09741350R; 09741400R; 09741450R; 09741500R; 09741550R; 09741600R; 09741650R; 09741700R; 09741750R; 09741800R; 09741850R; 09741900R; 09741950R; 09742000R

Broca HSS-CO de “haste reduzida” HSS-CO

HSS-CO



Broca HSS-CO DIN 338N com “haste reduzida”.



DADOS TÉCNICOS

ES Brocas de alto rendimiento, rectificadas, con contenido de cobalto, afilado en cruz y refuerzo total del alma. Mango reducido.

FR Foret pour fort rendement, rectifié avec de cobalt, aiguisé en croix et renforcement total. Embout réduit.

EN High-performance, contains cobalt, cross sharp point and totally reinforced body. Reduced shank.

IT Punta ad alto rendimento, rettificata, al cobalto, affilato a croce, con rinforzo totale dell'anima. Gambo ridotto.

PT Brocas de alto desempenho, retificadas, contendo cobalto, aguçadas em cruz e reforço total do interior. Haste reduzida.

Ref	Ø	
0974 1350R	13,50 mm	1
0974 1400R	14,00 mm	1
0974 1450R	14,50 mm	1
0974 1500R	15,00 mm	1
0974 1550R	15,50 mm	1
0974 1600R	16,00 mm	1
0974 1650R	16,50 mm	1
0974 1700R	17,00 mm	1
0974 1750R	17,50 mm	1
0974 1800R	18,00 mm	1
0974 1850R	18,50 mm	1
0974 1900R	19,00 mm	1
0974 1950R	19,50 mm	1
0974 2000R	20,00 mm	1