



CARACTÉRISTIQUES TECHNIQUES

Référence: 09750100; 09750150; 09750200; 09750225; 09750250; 09750300; 09750325; 09750350; 09750400; 09750425; 09750450; 09750500; 09750525; 09750550; 09750600; 09750650; 09750700; 09750750; 09750800; 09750850; 09750900; 09750950; 09751000; 09751050; 09751100; 09751150; 09751200; 09751250; 09751300

Forets en titane HSS TIN-DIN 338

HSS-TIN



ES Broca en acero rápido rectificadas, con recubrimiento de nitruro de titanio y afilada en cruz.

FR Foret en acier rapide rectifié, avec revêtement en nitrure de titane, aiguisé en croix.

EN High speed steel drill, titanium nitride coated and cross sharp point.

IT Punta in acciaio rapido rettificato, con rivestimento in nitruro di titanio, affilata a croce.

PT Broca de aço rápido retificado, com revestimento de nitreto de titânio e afiada em cruz.

Forets en titane, haute performance, rectifiés, revêtus de nitrure de titane.

HSS TIN DIN 338N 118°.

Pour aciers durs.

Couleur or



CARACTERÍSTICAS TÉCNICAS

Ref	Ø	
0975 0100	1,0 mm	10
0975 0150	1,5 mm	10
0975 0200	2,0 mm	10
0975 0225	2,25 mm	10
0975 0250	2,5 mm	10
0975 0300	3,0 mm	10
0975 0325	3,25 mm	10
0975 0350	3,5 mm	10
0975 0400	4,0 mm	10
0975 0425	4,25 mm	10
0975 0450	4,5 mm	10
0975 0500	5,0 mm	10
0975 0525	5,25 mm	10
0975 0550	5,5 mm	10
0975 0600	6,0 mm	10
0975 0650	6,5 mm	10
0975 0700	7,0 mm	10
0975 0750	7,5 mm	10
0975 0800	8,0 mm	10
0975 0850	8,5 mm	10
0975 0900	9,0 mm	10
0975 0950	9,5 mm	10
0975 1000	10,0 mm	5
0975 1050	10,5 mm	5
0975 1100	11,0 mm	5
0975 1150	11,5 mm	5
0975 1200	12,0 mm	5
0975 1250	12,5 mm	5
0975 1300	13,0 mm	5