



FICHA TÉCNICA


Artículo : 0605 0001 - 0605 0002 - 0605 0003 - 0605 0004 - 0605 0005
VÁLVULA ANTIRRETORNO

Válvula Antirretorno para líquidos.




Ref	Ø	Ø	Ø
0605 0001	M-5	M-5	1
0605 0002	1/8"	1/8"	1
0605 0003	1/4"	1/4"	1
0605 0004	3/8"	3/8"	1
0605 0005	1/2"	1/2"	1





 NBR: da -5°C a +70°C
 EPDM: da -40°C a +140°C

da 0,5 a 10 Bar
 Pressione minima d'apertura:
 0,025 Bar
 Pressione massima d'apertura:
 0,025 Bar

 Aria compressa e fluidi
 compatibili con i materiali
 costruttivi.

 Cilindrica gas BSPP ISO 228/1
 da G1/8" a G1"
 Metrica ISO 262 M5

 Circolazione dei fluidi in una
 sola direzione. Indicazione della
 direzione del fluido sul corpo.

 Corpo: ottone nichelato
 Otturatore: acciaio inox AISI 304
 Molla: acciaio inox AISI 302
 O-ring: NBR 70

CARATTERISTICHE

Realizzate con otturatore a sfera che
 garantisce il vantaggio di eliminare l'attrito dei
 componenti e contemporaneamente aumenta
 la durata nel tempo.



Prodotti conformi alla
 direttiva 1907/2006



Prodotti conformi alla
 direttiva EU 2015/863